

PeopleCounter Pro

"The New Extreme"

Part # 3002-35

Our Highest Value Counter.
Expandable When You're Ready
for More.



The PeopleCounter Pro Wall Mount Counter was introduced in early 2005. This is the Door Frame version of that hugely popular and expandable counter. This infrared beam interruption counter consists of two components; the IR transmitter and the IR receiver. The IR transmitter flashes high intensity IR which provides easy, instant alignment and installation.

The nature of these IR pulses is such that the IR receiver can distinguish them from any other source of IR. This characteristic allows the IR sensor to operate without interference from ambient lighting.

These extremely small counters, measuring only 1.7" x 3.1" x 0.8" (including mounting flange) and weighing only two ounces each, when applied to a surface facing each other, will cover a separation of **40** feet. This electrically powered counter comes with battery-backup so that **counting continues even when AC power is lost.**

An important feature of the PeopleCounter Pro is the ability to add wireless connectivity to the Walker Wireless line of BoostAccount Repeaters and CompuCount Servers, enabling counts to be viewed on a standard computer.

Key Advantages

- Everyone crossing the beam is counted. Our sensor is never confused by color or size.
- 3.6 V Lithium battery operation allows continuous counting even with loss of AC power.
- Small size, low weight, fast and easy installation.
- Count people across a 40 foot span.
- Integrated 6-digit LCD shows count data.
- Easy Upgrade Path to add wireless connectivity enabling counts to be viewed on a computer.
- One Year Warranty.

EXPANSION CAPABILITIES

Wireless Connectivity

A simple upgrade path will allow you to replace the electronic circuit board in the wall mount receiver to achieve wireless connectivity to our compatible BoostAccount and CompuCount equipment.

COMPUCOUNT

Collects and stores count data from up to 16 counters. An ethernet connection to your computer permits viewing of the data from any standard web browser. (Wireless connectivity required.)

BOOSTACOUNT

Pre-configured repeater to transmit the count data through walls and floors to the CompuCount.